



Active - GD

2 Trigger Controlled by Password/SMS
with 32 texts LCD keypad

GSM
AUTO DIALER



1 Password



24 Hours Tamper Provision



1 Electrical Appliance Control



2 Trigger, 2 Lines LCD Display Keypad



Arming / Disarming through SMS

Application



Fire Panel



DVR



Intrusion Panel

Features

- 2 Trigger Available NO, NC (Normally Open/Close)
- 15 Texts SMS Option Available
- On Board Keypad With 32 Bit Lcd
- Arm/Disarm Through Password / SMS
- Changeable User Password
- Instant Call/ SMS Alert For Trigger Open
- Individual Voice And Text Message Available For Both Trigger
- 20 Sec Recording Time For Individual Voice Message
- Built-In Gsm Communicator
- Memory Available To Store 10 Phone Numbers
- Receives SMS While Arm/Disarm
- Arm/Disarm By SMS Can Be Controlled By First Three Admin Numbers
- Balance Status Can Be Checked By SMS
- Recorded Message Playback Speaker Provision Available
- Control Panel Door Tamper Available
- External Relay For Trigger Mode And Application Mode
- In Application Mode Relay Can Be Operated By SMS
- Used For Both Intrusion And Fire Alarm Panel

Specifications

POWER SUPPLY	
Maximum Power Consumption	24 Watts
DC /AC Main Supply	12-24 V / 2 amps
ZONES	
Zone Response Time	< 500 Millisecond
Zone Loop Resistance	< 1 kilo Ohm For Normally Closed
Max Length of Sensor Cable (multi core cable)	150 m (Depends on cable resistance)
GSM Antenna	3 db required
RELAY-NORMALLY CLOSED	
Max Voltage/ current ratings	AC 240 V/5 A
ENVIRONMENTAL	
Environment	Residential/ Commercial/ Light Industrial
Max Humidity	95% Non-Condensing
Operating Temperature	0°C To 45°C
Storage Temperature	-20°C~+ 60°C
PHYSICAL	
Colour	Grey Coloured Metal Box
Control Panel Dimensions(mm)	(H X W X L) = 150 X 45 X 130
Weight	570 g



